

1. ~~Unit~~ Displacement unit

1. Displacement unit, for example for supply, manipulation, joining or control systems of mounting parts with components that can be adjusted relative to one another by means of a drive unit and with at least one guiding device for at least one of the components and a control unit, characterised in that at least one member (8) of the control unit (7) used for processing logic information or bus information (command) is integrated into the drive unit (5) and/or into at least one of the components (3; 4) and/or is mounted on one of the components (3; 4).
2. Displacement unit according to claim 1, characterised in that the control unit (7) comprises at least one control module (9) and/or one or more switching modules (10) assigned to the control module (9).
3. Displacement unit according to claim 1 and/or 2, characterised in that the control unit (7), in particular the control module (9) and/or the switching modules (10), comprises inputs (52), for example for signals and/or commands of a central control unit (134) and/or the switching module (10) and/or the signalling and/or monitoring members (16) and/or control units (7) of further displacement units (1) and/or external input and/or output devices (79) and/or drive units (5) and/or power.
4. Displacement unit according to one or more of the preceding claims, characterised in that the inputs (52) are connected by single point plugs with single lines and/or by at least one multipoint plug with at least one multipoint line and/or are connected by a bus connector plug (53) to a bus line (97) designed as a central connection line.
5. Displacement unit according to one or more of the preceding claims, characterised in that the control unit (7), in particular the control module (9) and/or the switching modules (10), comprises outputs (54), for example for signals and/or commands to the central control unit (134) and/or to the switching modules (10) and/or to the signalling and/or monitoring members (16) and/or to control units (7) of additional displacement units (1) and/or to external input and/or output devices (79) and/or to drive units (5) and/or for power.

6. Displacement unit according to one or more of the preceding claims, characterised in that the outputs (54) are connected by single point plugs to single lines and/or via one or an additional multipoint plug to one or an additional multipoint line and/or via one or an additional bus connector plug (53) to one or an additional central connection line.
7. Displacement unit according to one or more of the preceding claims, characterised in that the control unit (7), in particular the control module (9) has a memory (131) for storing, in particular individual movements.
8. Displacement unit according to one or more of the preceding claims, characterised in that the control unit (7), in particular the control module (9), has a logic unit comprising at least one logic element (139), which forms the member (8), which processes logic information and/or commands and/or bus information, for example for determining and/or monitoring the positions of the components (3; 4) and/or the displacement parameters of the drive unit (5).
9. Displacement unit according to one or more of the preceding claims, characterised in that the logic element (139) of the control unit (7), in particular the control module (9) is designed as a microprocessor (127) which is connected by conductors (128) or flexible control lines (49) with for example an interface (129) for the bus connector plug (53) and/or an evaluation unit (130) and/or a memory (131) and/or an external interface (129) and/or a driver (132) and/or a D/A converter (133).
10. Displacement unit according to one or more of the preceding claims, characterised in that the control unit (7) has a control power source, in particular a battery, an accumulator and/or an interface for an external power source.
11. Displacement unit according to one or more of the preceding claims, characterised in that at least one logic element (139) is designed as an electronic module, for example a microprocessor (127) or a PC or SPS.
12. Displacement unit according to one or more of the preceding claims, characterised in that at least one switching module (10) and/or one logic element (139) is designed for example as a pneumatic valve (11) and/or relay and/or contactor.

13. Displacement unit according to one or more of the preceding claims, characterised in that the control unit (7), in particular the switching module (10) is connected to at least one drive unit (5) designed for example as a pneumatic drive (12), hydraulic drive, servomotor drive, electric motor drive, manual drive or piezo drive.
14. Displacement unit according to one or more of the preceding claims, characterised in that the drive unit (5) has one or more transmitting elements which are connected to at least one component (3;4) and which are in the form for example of couplings, toothed belts, racks, spindles, gears or links.
15. Displacement unit according to one or more of the preceding claims, characterised in that component (4) is arranged to move relatively on a preferably frame-shaped, other component (3) by means of a guiding device (6) designed as a linear guide (119) and/or rotary and/or gear guide.
16. Displacement unit according to one or more of the preceding claims, characterised in that at least one component (3; 4) comprises one or more standardised interfaces (95) for control lines (49) and/or lines (50) of further assembly and/or processing devices and/or additional displacement units (1) and/or for power and/or of control units (7).
17. Displacement unit according to one or more of the preceding claims, characterised in that in the region of the interfaces (95, 101, 129) inputs (52) and/or outputs (54) of the control unit (7) are arranged, which are line-connected by plug connectors, in particular coupling devices with at least one control unit (7) of an additional displacement unit (1).
18. Displacement unit according to one or more of the preceding claims, characterised in that the switching modules (10) are arranged on the drive unit (5) or are integrated into the latter.
19. Displacement unit according to one or more of the preceding claims, characterised in that the switching modules (10) are designed as valve cartridges (115), which are arranged in a guiding device (103) of the drive unit (5).

20. Displacement unit according to one or more of the preceding claims, characterised in that the switching module (10), in particular the valve cartridge (115), comprises a control module (9).
21. Displacement unit according to one or more of the preceding claims, characterised in that the pneumatic drive (12) designed as a pneumatic cylinder (13) has end face closing elements (14), which are positioned so as to be adjustable relative to one another on or in a cylindrical pipe (15) of the pneumatic cylinder (13).
22. Displacement unit according to one or more of the preceding claims, characterised in that the signalling and/or monitoring members (16), are for example limit switches and/or proximity switches (17) and/or displacement measuring systems and/or position detecting systems and/or vibration sensors and/or force sensors.
23. Displacement unit according to one or more of the preceding claims, characterised in that the component (3; 4) is secured by a securing device (122) arranged detachably on the other component (4; 3) in at least one direction of movement.
24. Displacement unit according to one or more of the preceding claims, characterised in that the securing device (122) is formed for example by a damping device (123), a braking device or an arresting device.
25. Displacement unit according to one or more of the preceding claims, characterised in that the control unit (7) comprises at least one display element (75), which is designed for example as a display (76) with text, number display, light-emitting diodes or as an acoustic information element.
26. Displacement unit according to one or more of the preceding claims, characterised in that the control unit (7) comprises an input device (77), for example in the form of a keyboard (78) or a touch screen.
27. Displacement unit according to one or more of the preceding claims, characterised in that the touch screen combines the display element (75) with the input device (77).

28. Displacement unit according to one or more of the preceding claims, characterised in that the interfaces (95, 101, 129) and/or the inputs (52) and/or the outputs (54) are designed as plug-in coupling devices.
29. Displacement unit according to one or more of the preceding claims, characterised in that at least one component (3;4) comprises an electric distribution bus bar (72) and/or a pneumatic distribution bar (55).
30. Displacement unit according to one or more of the preceding claims, characterised in that the electric distribution bus bar (72) and/or the pneumatic distribution bar (55) comprises control lines (49) and/or lines (50) and/or channels (61), which are preferably integrated into the component (3;4).
31. Displacement unit according to one or more of the preceding claims, characterised in that the switching modules (10) are arranged on and/or in the pneumatic distribution bar (55), which are preferably plug connected by openings (63) to openings (60) arranged in the pneumatic distribution bar (55).
32. Displacement unit according to one or more of the preceding claims, characterised in that one component (3;4) comprises at least one securing device (118) for the signalling and/or monitoring members (16), preferably in the form of a guiding device (103).
33. Displacement unit according to one or more of the preceding claims, characterised in that the signalling and/or monitoring members (16) and/or the switching modules (10) and/or the control modules (9) are arranged displaceably on the electric distribution bus bars (72), in the form of a bus line (97) for example.
34. Displacement unit according to one or more of the preceding claims, characterised in that the signalling and/or monitoring members (16) comprise control modules (9) and/or logic elements (139).
35. Displacement unit according to one or more of the preceding claims, characterised in that the input and/or output device (79), is designed for example as a keyboard and/or as a

36. Displacement unit according to one or more of the preceding claims, characterised in that the data is transmitted from the control unit (7) to the control unit (134) and/or from the individual components of the control unit (7) to the latter wirelessly, for example optically by means of lasers or for example by means of infrared or ultrasound.

38. Displacement unit according to one or more of the preceding claims, characterised in that the data glove is connected preferably couplably via inputs (52) and/or outputs (54) to the control unit (7) and/or the control unit (134).

40. Method according to claim 39, characterised in that for each displacement unit a learning mode is executed in which the actual value of a prespecified target value is determined, whereupon after completing the learning mode of the last displacement unit said actual values are compared and are selected as a target value.

- INS.
DZ